

Архангельск (8182)63-90-72 Астана +7(7172)727-132 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Липецк (4742)52-20-81 Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород 429-08-12 Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань Петербург (812)309-46-40 Саратов (845)249-38-78 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-9333
Единый адрес для всех регионов: ixb@nt-rt.ru || www.ibix.nt-rt.ru



FUBIX

**THE FIRST AND ONLY MULTI PURPOSE
BATTERY POWERED PRESSURE JOINT MACHINE
LIGHT, COMPACT AND SIMPLE TO USE**

Especially suitable for filling all joints types on outer facades in brick, stone, rock, etc. For spraying, injection, micro-injection and pumping any kind of cement compounds or premixed mortars, glues, resins, polyurethane, etc...



Extrusion jointing



Injection with
pressure indication



Spraying

ACCESSORIES



Jointing lance



Flat nozzle injector
for extrusion jointing



Pressure injection lance



Spraying lance



Suction pipe



Power supplier 220V - 12V



Pressure micro-injection kit



Suction pipe



Pressure switch



FUBIX - P60

TECHNICAL SPECIFICATION

- Motor C.C. 65W
- Powered by 12V 12A
- Voltage 220V - 12V
- Remote control with speed regulator
- Start, stop and reverse
- Capacity of standard hopper LT. 13
- Capacity 0/360 LT/h
- Calibrated for inert particles from 0 to 5 mm
- Height cm. 37
- Length cm. 40
- Width cm. 40
- Weight kg. 15



FUBIX - P80

TECHNICAL SPECIFICATION

- Motor C.C. 600W
- Powered by 24V
- Voltage 220V - 24V
- Remote control with speed regulator
- Start, stop and reverse
- Capacity of standard hopper LT. 20
- Capacity 0/700 LT/h
- Calibrated for inert particles from 0 to 5 mm
- Height cm. 37
- Length cm. 40
- Width cm. 50
- Weight kg. 20

FUBIX - P100

TECHNICAL SPECIFICATION

- Motor C.C. 65W
- Powered by 12V 12A
- Voltage 220V - 12V
- Remote control with speed regulator
- Start, stop and reverse
- Capacity of standard hopper LT. 13
- Capacity 0/180 LT/h
- Calibrated for inert particles from 0 to 5 mm
- Height cm. 37
- Length cm. 40
- Width cm. 40
- Weight kg. 14